

### Slangupprullare Högtryck

Typ	Arb.tryck max Bar	Anslut. svivel	Slanglängd max.						Vikt kg	Dimension BxLxH cm	svängbart fäste
			1/4"	3/8"	1/2"	3/4"	1"	1 1/4"			
AV1000	200	1/2"	15	15	15				13	25x50x48	ST 15
AV1100	200	1/2"	20	20	20				18	28x50x48	ST 20
AV3400	200	1/2"		25	25				28	34x61x66	ST 34
AV3500	200	1/2"		35	35				28	34x61x66	ST 30
AV4000	200	1/2"		40					33	45x55x63	ST 30
AV4500	200	1/2"			40				26	45x55x63	ST 22
AV3550	200	1/2"	50	60	50				28	34x61x66	ST 30
AV6000	200	1/2"		60	60				50	45x55x63	ST 60
AV6200	200	1/2"		60	60				48	60x60x60	x
AV6300	200	1/2"	100	100	100				60	60x60x60	x

Alla rullar kan erhållas med 400 eller 600 bars svivel mot tillägg

Alla rullar finns i rostfritt eller lackerat utförande

### Slangupprullare Lågtryck

Typ	Arb.tryck max Bar	Anslut. svivel	Slanglängd max.						Vikt kg	Dimension BxLxH cm	Svängbart fäste
			1/4"	3/8"	1/2"	3/4"	1"	1 1/4"			
HP15	200	1/2"	15	10					15	40x30x40	STHP15
AV1000	80	1/2"		15	15				13	25x50x48	ST 15
AV1100	80	1/2"		20	20				18	28x50x48	ST 20
AV1200	80	1"				13	8		14	28x61x54	ST 20
AV1300	80	1"				18	15		22	45x55x63	ST 22
AV3400	80	1/2"		25	25				28	34x61x66	ST 34
AV3500	80	1/2"		35	35				28	34x61x66	ST 30
AV3501	80	1"				20	13		28	34x61x64	ST 30
AV3502	80	1"				25	15		28	34x61x62	ST 30
AV3503	80	1"				35	25		28	34x61x62	ST 33
AV3550	80	1/2"		60	50				28	34x61x66	ST 30
AV5000	80	1"				30	25		40	55x57x63	ST 50
AV6001	80	1"				40	30		51	60x60x60	x
AV6002	50	1 1/4"						20	52	60x60x60	x
AV6003	50	1 1/2"							15	60x60x60	x
AV6004	50	1"							20	60x60x60	x
AV6005	50	1"						10	52	60x60x60	x
AV6030	80	1"					30		50	60x60x60	ST 60
AV6301	80	1"				50			60	60x60x60	x

Alla rullar finns i rostfritt eller lackerat utförande

### Kapslade slangupprullare med slang Vatten-Luft

Typ	Arb.tryck max bar	Anslut.	Slanglängd		Vikt	Dimension BxLxH cm
			1/4"	3/8"		
35810	10	1/4"	10		7	32x53x60
35815	10	1/4"	15		7	32x53x60
35812	10	3/8"		10	7	32x53x60

### Motoriserade slangupprullare

Typ	Arb.tryck max Bar	Anslut. svivel	Motor	Slanglängd max.				Vikt kg	Dimension BxLxH cm
				3/8"	1/2"	3/4"	1"		
Reelsafe 13	350	1/2"	EI	20	15			21	43x40x48
Reelsafe 15	350	1/2"	EI	40	30	25	15	29	48x55x63
AVPN 0	200	1/2"	Tryckluft		100			50	60x60x60
AVPN 2	80	1"	Tryckluft			50	35	50	60x60x60
AV6500	200	1/2"	Hydralik		100			50	80x62x63
AV6501	80	1"	Hydralik			50		50	80x62x63

### Manuella slangupprullare

Typ	Arb.tryck max bar	Anslut. svivel	Slanglängd max					Max Temp	Vikt kg	Dimension BxLxH cm
			1/4"	3/8"	1/2"	3/4"	1"			
AVM9810	200	1/2"	50	35	25			90	10	45x35x500
AVM9812	200	1/2"	80	60	40			90	10	35x45x500
AVM9815	20	1"				15	13	90	10	35x45x500
AVM9817	20	1"				25	20	90	10	45x45x50
B-12	250	3/8"	25	12				150	10	37x40x620
v-25	250	1/2"	45	25				150	11	67x40x35
V-50	250	1/2"		50				150	15	77x40x45
MH-50	250	1/2"		50	40			150	17	68x45x98
ML-50	15	3/4"		50	40	20		150	17	68x45x98
MH-100	250	1/2"		100	70			150	19	68x70x98
ML-100	15	1/4"		100	70	50		150	19	68x70x98

### Elkabelrullar

Typ	El.kabel dim.	Längd m	Max V	Max A	Max kw	Vikt kg	Dimension BxLxH cm
811200	3x1,5	10	230		2	3,8	28x28x19
811020	3x1,5	15	230		2	4,5	29x29x21
820705	3x1,5	25	230		2	8,3	42x39x23
CR4020	4x2,5	20	400	16	6	15	25x50x58
CR4030	4x2,5	30	400	16	6	15	25x50x58